





Hi-Temp Wet Tantalum Capacitor

Shanghai Green Tech Co.,Ltd.

CA382 series

3, Table 2 General characteristics

Rated Vol. (V)	A Derated Vol. 125 (V)	B Derated Vol. 200 (V)	Nominal Cap. (F)	Dissipation Factor +25 +85 +200 (%)	Leakage current (A)		Impedance 100Hz -55 ()	Cap change rate (%)			85 40KHZ AC Ripple current (mA)	Case Code
					+25	+85 +125			-55	+85		
6	4	3.6	30	7	1	2	100	-40	+11	+15	820	T1
			68	12			60		+14	+18	960	
			140	17			40		+20	1200		
			270	30		7	25	-44	+18	+25	1375	T2
			330	30	8	20	+14		+20	1800		
			560	45	13	25	-64	+18	+25	1900	T3	
			1200	90	3	14	20	-80	+25	+30		2265
8	5	4.8	25	7	1	2	100	-40	+11	+15	820	T1
			56	10			59		+14	+18	900	
			120	15			50		-44	+18	+20	
			220	30		7	30	1370				
			290	30	2	6	25	-64	+25		1770	T3
			430	36		14	25				1825	
			850	50	4	16	22	-80	+25	+30	2330	T4
10	7	6	20	5	1	2	175	-32	+11	+15	820	T1
			47	11			100	-36	+14	+18	855	
			100	12			4			60	+20	
			180	20		7	40	+25		1365		
			250	25	2	10	30			-40	1720	T3
			390	25		16	25	-64	+18	1800		
			750	40	4		23	-80	+25	+30	2360	T4

Please read the important notes and cautions at the end of this document.

Document Number:150142 Revision:17-Apr.-15 <http://www.greentechee.com>

page 2

GT CAP®



Table 2 General characteristics

Rated Vol. (V)	A Derated Vol. 125 (V)	B Derated Vol. 200 (V)	Nominal Cap. (F)	Dissipation Factor +25 +85 +200 (%)	Leakage current (A)		Impedance 100Hz -55 ()	Cap change rate (%)			85 40KHZ AC Ripple current (mA)	Case Code
					+25	+85 +125		-55	+85	+200		
30	20	18	8	4	1	2	275	-16	+8	+12	640	T1
			15	5			175	-20	+11	+15	780	
			40	8			65	-24			1120	T2
			68	11			60				1285	
			100	15	2	10	40	-28	+11	+18	1450	T3
			150	20		15	35	-48	+13	+25	1525	
			300	25	8	32	25	-60	+25	+35	1950	T4
50	30	30	5	3	1	2	400	-16	+5	+9	580	T1
			10	4		2	250	-24	+8	+12	715	
			25	7		5	95	-20	+11	+15	1005	T2
			47	10		8	70	-28	+13	+18	1155	
			60	10	2	10	45	-16	+11	+15	1335	T3
			82	12		12	45	-32	+13	+18	1400	
			160	15	8	30	27	-50	+25	+30	1900	T4
60	40	36	4	2.8	1	2	550	-16	+5	+9	525	T1
			8.2	4		2	275	-24	+8	+12	625	
			20	6		5	105	-16	+11	+15	930	T2
			39	8		8	90	-28			1110	
			50	9	2	10	50	-16			1330	T3
			68	10		10	45	-32			1365	
			140	12	8	30	28	-40	+20	+25	1850	T4
			*560	50	30	160	25	-60	+40	+50	2800	T5
75	50	45	3.5	2.5	1	2	650	-16	+5	+9	525	T1
			6.8	3.5		2	300	-20	+8	+12	610	
			15	5		5	150	-16			890	T2
			33	8		9	90	-24	+11	+18	1000	
			40	8	2	10	60	-16		+15	1250	T3
			56	10		12		-28		+18	1335	
100	65	60	110	10	9	30	29	-35	+20	+25	1850	T4
			2.5	2	1	2	950	-16	+7	+10	505	T1
			4.7	3		2	500	-20			565	
			11	5		4	200	-16			835	T2
			22	6		9	100	-24	+8		965	

